

STREETSMARTV2™

Part Number: GS-3-SS2

DESCRIPTION

STREETSMARTV2 by GRIDSMART gives traffic managers the ability to adjust traffic flow strategies based on real-time congestion analytics and travel-time conditions. V2 captures traffic cabinet data and allows users to report on signal performance metrics, travel time, and origin destination. V2 features a sleek, rugged design with a powder coated aluminum housing for easy installation and lasting service.

V2 is the evolution of STREETSMART and a completely new product built on GRIDSMART reliability, hardware, and firmware. STREETSMART is no longer available.

SPECIFICATIONS

- Detector I/O: TS1 or TS2
- Connectivity: Wide Area Network (WAN) and LTE
- Dimensions: 10.8" x 1.8" x 7"
(27.4 x 4.5 x 17.8 cm)
- Weight: 2.7 lbs (1.2 kg)
- Power: 120/240 VAC 50/60 Hz
- Capture Modality: Wi-Fi
- Environmental: -29°F to 165°F (-34°C to 74°C)
0%-95% Non-condensing Humidity
5-30Hz Vibration
10G Shock
- Standards: NEMA TS2
- Regulatory: FCC Class A



FEATURED DATA

- Travel Time
- Origin Destination
- Signal Performance Metrics